

22" (21.5" viewable) Full HD Multimedia LED Monitor with HDMI

ViewSonic®
See the difference® 

Stunning Color Performance with SuperClear® MVA Technology

VA2265Smh



Available for this model:
**Privacy Filter
Screen Protector**
VSPF2150
(Sold Separately)

The ViewSonic® VA2265Smh 22" (21.5" viewable) LED backlit, HD widescreen monitor delivers stunning images driven by our latest SuperClear® MVA panel technology and a 3000:1 contrast ratio. With HDMI 1.4 and VGA support and built-in speakers, this monitor supports a variety of devices from your PC to your latest gaming device. Our exclusive ViewMode™ setting optimizes the monitor for a variety of applications from gaming to editing your next novel. Integrated Flicker-free and Blue Light Filter technology helps eliminate eye-strain during extended viewing periods. The VA2265Smh includes a VESA-mountable design to provide additional mounting options. Backed by our 3-year limited warranty and one of the industry's best pixel performance policies, the VA2265Smh packs an amazing amount of performance in a sleek streamlined design.

Key Features:

SuperClear® MVA technology for stunning color performance and wide-angle viewing

Flexible connectivity options include HDMI and VGA

Full HD1080p resolution provides superior pixel performance

Exclusive ViewMode technology delivers superior color rendering and intuitive settings

Flicker-free and Blue Light Filter technology for more comfortable viewing

Designed for:

Home

Business

22" (21.5" viewable) Full HD Multimedia LED Monitor with HDMI

ViewSonic®
See the difference® 

VA2265Smh



Specifications

LCD PANEL	Type	Color a-Si Active Matrix TFT LCD
	Display Area	18.7" horizontal x 10.5" vertical; 21.5" diagonal
	Optimum Resolution	1920x1080
	Brightness	250 cd/m ² (typ.)
	Contrast Ratio	3,000:1 (typ.)
	Viewing Angles	178° horizontal, 178° vertical
	Colors	16.7M (6bit + Hi-FRC)
	Response Time	6.5ms (GTG)
	Backlight	White-light LED
	Backlight Life	40,000 hours (min.)
	Panel Surface	Anti-glare, hard-coating (3H)
VIDEO INPUT	Digital	VGA, HDMI
	Frequency	Fh: 24~82kHz, Fv: 50~75Hz
AUDIO OUTPUT	Speakers	2-watt (x2)
	Sync	Separate Sync, Composite Sync, Sync on Green
COMPATIBILITY	PC	Up to 1920x1080 non-interlaced
	Mac®	Up to 1920x1080
CONNECTOR	Video In	VGA, HDMI
	Audio In	3.5mm mini jack
	Headphone	3.5mm mini jack
	Power	External power adapter
CONTROLS	Front Panel Buttons	Power, 1, Up, Down, 2
	OSD	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

ERGONOMICS	Tilt	Forward 5° / Back 20°
POWER	Voltage	AC 100~240V (universal), 50 / 60Hz
	Consumption	22W (typ.) / 30W (max.)
	Optimize	17W (typ.)
	Conserve	13W (typ.)
OPERATING CONDITIONS	Temperature	32~104° F (0~40° C)
	Humidity	10~90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with Stand	20.1 x 15.3 x 7.6 in. / 510.7 x 387.6 x 193.1 mm
	Physical without Stand	20.1 x 12.6 x 1.9 in. / 510.7 x 319.4 x 47.2 mm
	Packaging	22.4 x 15.0 x 5.0 in. / 569 x 382 x 128 mm
WEIGHT	Net with Stand	7.9 lb. / 3.6 kg
	Net without Stand	6.7 lb. / 3.0 kg
	Gross	10.2 lb. / 4.6 kg
WALL MOUNT	VESA	100 x 100mm
REGULATIONS		CE CB, WEEE, RoHS, TCO 6.0, Erp, WHQL, cUL, ENERGY STAR, FCC-B, EPEAT Silver
RECYCLE/DISPOSAL		Please dispose of in accordance with local, state, or federal laws
WARRANTY		Three-year limited warranty on parts, labor and backlight

Optional Accessories

ViewSonic HDMI male to DVI male cable 1.8 meter CB-00008948

What's in the box?

VA2265Smh monitor, Power cable, VGA cable, Quick Start Guide



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.